DISPLAY FABRIC

Product Code: STC 2300

Product Description

- Fabric is smooth and soft for a perfect textile hand feel
- Special construction of the fabric provides higher opacity at a lighter weight.
- Wrinkle free fabric for easy transportation and crease free applications.
- Printable on dye direct, paper transfer, UV and latex printers

PRODUCT PROPERTIES (TYPICAL VALUES)

Particular	Test Mehtod	Average Values
Total Weight	DIN EN ISO 2286-2	210gsm
Base Fabric	DIN 60001	Polyester
Yarn Dtex	DIN EN ISO 2060	83 x 55 x 55 dtex
Weave Method	N/A	Wrap-Knitted 3 bar
White Point	CIE86/ASTME313-00	$\geq$ 133
Shrinkage	N/A	< 2% (190$^{°}$c , 1 min)
Flame Resistance	DIN 4102-1	B1
Fixation Temperature	N/A	190$^{°}$c - 210$^{°}$c, 1-2 min
Transfer Temperature	N/A	190$^{°}$c - 210$^{°}$c, 1-2 min
Yellowing Temperature	SUPRKC REX-C400	230$^{°}$c
Maximum Width		3.20 meter
Ink Compatibility		Dye Transfer & Direct UV / Latex

The above specifications are based on average results during the testing procedures. No liability will be accepted for errors and in no circumstances shall STC Graphics Canada will be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet and usage of the material, as we have no control over usage of the above material. Users are advised to check the suitability of the product prior to its intended use.

When **IMAGE** *matters*™