

TECHNICAL DATA SHEET

MESH FLAG

Product Code: STC 2500

Product Description

- 100% polyester mesh fabric

- Semi gloss finish

- Soft texture

- Good penetration and reverse effect

PRODUCT PROPERTIES (TYPICAL VALUES)

Particular	Test Mehtod	Average Values
Total Weight	DIN EN ISO 2286-2	115gsm
Base Fabric	DIN 60001	Polyester
Yarn Dtex	DIN EN ISO 2060	55 x 55 x 55 dtex
Weave Method	N/A	Wrap knitted 3 bar
White Point	CIE86/ASTME313-00	≥122
Shrinkage	N/A	< 2% (190°c , 1 min)
Flame Resistance	DIN 4102-1	B1
Fixation Temperature	N/A	190°c - 210°c, 1-2 min
Transfer Temperature	N/A	190°c - 210°c, 1-2 min
Yellowing Temperature	SUPRKC REX-C400	240°c
Maximum Width		3.20 meter
Ink Compatibility		Dye Direct, Dye Transfer

The above specifications are based on average results during the testing procedures. No liability will be accepted for errors and in no circumstances shall STC Graphics Canada will be liable for any loss or injury arising directly or as a consequence of the publication of this data sheet and usage of the material, as we have no control over usage or installation of the above material. Users are advised to check the suitable of the product prior to its intended use.

When IMAGE matters

email: sales@stcgraphics.com